

CanSeal SL is a professional grade one-part, self-leveling, sealant/coating formulated for low movement joint and coating applications requiring quick cure and excellent weatherability, including high UV resistance. **CanSeal SL** reacts with moisture to form a strong yet flexible all-weather seal.

CanSeal SL is tough, elastic and waterproof. It bonds aggressively to steel, aluminum, ceramics, coated metal, Styrofoam®, EPS, glass, wood and many plastics. **CanSeal SL** is suited for many applications requiring adhesion to concrete and cementitious building materials.

CanSeal SL can be used in damp concrete joints, however pooled water and surface frost should be removed before application. Installation in high humidity conditions is acceptable.

Benefits:

- Odor Free
- Primerless bonding to most surfaces
- Permanently elastic to -40°C
- Paint compatible
- Non-flammable
- Solvent and isocyanate free, 100% solids
- Fast curing
- Excellent fuel and solvent resistance

Physical Properties:

Basic Material	Proprietary Polymer
Consistency	Self-leveling fluid
Color	Black, White and Limestone
Odor	Nil
Components	1
Type	Elastic
Specific Gravity	1.7
Solvent Percentage	0
Isocyanate Percentage	0
Shelf Life	11 months in unopened containers stored between 40° and 80° F.

Approximate Performance Properties:

Shear Strength	>215psi (7 day ambient cure)	ASTM D-412
Elongation at Break	160 %+ (7 day ambient cure)	ASTM D-412
Hardness Shore A	53 (14 day ambient cure)	ASTM C-661
Initial Skin Forming	23 minutes	
Accelerated Weathering	No cracking	
Stain Testing	No Staining	
Low Temperature Flex	-20°	---PASS---
QUV Panel Test	4000 hours B-bulb	No change in physicals
Service Temperature	- 40° to 200° F, temporarily resistant to 390°	

Disclaimer: The information we provide is accurate to the best of our knowledge, but we do not assume any liability as to its accuracy or completeness. We do not guarantee that any hazards that we may mention are the only hazards that exist. User is responsible to determine the suitability of this product for user's intended application. User is responsible for determining that he can meet all applicable health and safety standards and regulations. We have no control over transportation, storage, handling and use of product and will not be liable for any damages resulting from their use.

Manufactured in the USA for:

**FORM &
BUILD** SUPPLY
www.formandbuild.com